

# Фонари ручные взрывобезопасные карманные TR, TS

## Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: [wft@nt-rt.ru](mailto:wft@nt-rt.ru) || сайт: <https://wolfsafety.nt-rt.ru/>

## **ATEX TORCH**

The ATEX Safety Torch is a reliable, simple and cost effective portable light and is available with a straight or right-angle body style and Vacuum or Xenon bulbs and is CE marked to the ATEX directive and IECEx certified for safe use in Zones 1 and 2 potentially explosive gas, vapour and mist atmosphere, where a T6 or T4 class permits, and Zones 21 and 22 dust atmospheres, with certified maximum surface temperatures of 65°C or 95°C.



### **Product Information**

**TR-24B, TR-26B, TS-24B, TS-26B**

**ZONES: 1, 2, 21 AND 22**

T4 models give outstanding light output using advanced, long life xenon bulbs, set in a high quality parabolic reflector, coupled with alkaline cell approval, giving up to 12 hours of light output. Alternatively T6 allows use in any Zone 1 or 2 atmospheres, with optimum light output in this temperature class, and a 5 hour duration.

The compact torch design has a high-grip ergonomic form with easy single-handed switching, even with gloved hands. The torch body offers high strength, and proven impact resistance even at sub zero temperatures, using carefully selected thermoplastic resins with excellent chemical resistance. Additionally, the rubber armoured lens ring and end cap give enhanced grip and shock protection. The lens is scratch and chemical resistant.

The torch is sealed dust tight and protected from water immersion, with a certified IP67 enclosure. Right angle models incorporate a replaceable high strength thermoplastic belt clip for hands free use. Both models allow straightforward battery and bulb replacement, a spare bulb is fitted in the bulbholder for quick and convenient replacement. All models are supplied with wrist straps and clip rings.

### **IMPA Codes**

79 22 61 - TS-26, 79 22 62 - TR-26

79 22 63 - TS-24, 79 22 64 - TR-24

## **TEX SAFETY TORCH WITH LED**

The Wolf ATEX Safety Torch with LED is an ATEX and IECEx certified primary cell LED Safety Torch using the latest technology to give excellent performance, robustness and reliability for safe use in Zones 1 and 2 potentially explosive gas and Zones 21 and 22 dust atmospheres (TR/TS-30+). A Zone 0 version is also available (TR/TS-35+). Group I approval for use in mining applications.



### **Product Information**

**TR-30+, TS-30+, TR-35+, TS-35+**

**ZONES: 0, 1, 2, 20, 21 AND 22**

This high strength torch, available with a straight or right angle body, is extremely robust and reliable, with proven shock protection, even at sub zero temperatures, rubber armoured lens ring and end cap, scratch and chemical attack resistance lens - all sealed dust tight and protected from water immersion, with an IP67 enclosure.

The compact, lightweight and ergonomic torch body gives enhanced grip and comfort for the user with easy single-handed switching, even with gloved hands, plus the replaceable high strength clip (on the right angle model only) allows for hands free use. Supplied as standard with wrist strap and clip ring.

Its unique optics deliver a piercing white spot beam combined with a wide-angle flood of fringe light from a high power 'fitted for life' LED giving a peak of up to 130 lumens light output. Two D/LR20 primary alkaline cells provide a light duration of up to 17 hours. With a low battery power indicator allows a user to monitor the state of battery charge, a red flashing light is emitted through the side of the torch body while battery power and light output is high, but

switching to continuous red when battery and light output is low, warning battery replacement is required.

#### NSN Codes

6230-99-9816738 - TR-35+MOD

Download Product Information Sheet.

- **Different Zones**

Zones 0, 1 and 21

- **Bespoke optics**

Medium spot beam with wide-angle flood of fringe light

- **Low maintenance**

Full range of spare parts available

#### Features & Benefits

- ATEX and IECEx certified for Zones 1 and 21; a Zone 0 version is also available
- High power 'fitted for life' LED for outstanding light output, no bulb replacement required
- Medium spot beam with wide-angle flood of fringe light
- Compact and lightweight ergonomic torch design, straight and right-angle versions
- Up to 130 lumens light output with up to 17 hours duration
- 2 x 1.5V D/LR20 primary cells with low power indicator
- Supplied with wrist strap and clip ring
- Very low maintenance, quick and easy parts replacement
- Group I Mining Approval

#### Technical Information

| Product Reference                   | TR-30+                                                                                       | TS-30+                                                                                         | TR-35+                                                                                             | TS-35+                                                                                                    |
|-------------------------------------|----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Product Description                 | Primary Cell LED Right Angle or Straight Safety Torch                                        |                                                                                                |                                                                                                    |                                                                                                           |
|                                     | Right Angle<br>Zone 1 & 21                                                                   | Straight<br>Zone 1 & 21                                                                        | Right Angle<br>Zone 0 & 21                                                                         | Straight<br>Zone 0 & 21                                                                                   |
| Code (ATEX & IECEx)                 | I M2/II 2GD Ex ib<br>I Mb/IIC T4 Gb (-<br>30°C ≤ Ta ≤<br>40/55°C)<br>Ex ib IIIB T130°C<br>Db | I M2/II 2GD<br>Ex ib I<br>Mb/IIC T4 Gb<br>(-20°C ≤ Ta ≤<br>40/55°C)<br>Ex ib IIIB<br>T130°C Db | I M1/II<br>1G2D Ex ia<br>I Ma/IIC T4<br>Ga (-30°C<br>≤ Ta ≤<br>40/55°C)<br>Ex ib IIIB<br>T130°C Db | I M1/II<br>1G2D Ex<br>ia I Ma/IIC<br>T4 Ga (-<br>20°C ≤ Ta<br>≤<br>40/55°C)<br>Ex ib IIIB<br>T130°C<br>Db |
| Type of Protection                  | 'ib' intrinsic safety                                                                        |                                                                                                |                                                                                                    | 'ia' intrinsic<br>safety                                                                                  |
| Area of<br>Classification (Gas)     | Zones 1 & 2 Gas Groups IIA, IIB IIC                                                          |                                                                                                |                                                                                                    | Zones 0, 1<br>& 2 Gas<br>Groups<br>IIA, IIB IIC                                                           |
| Temperature<br>Classification (Gas) | T4                                                                                           |                                                                                                |                                                                                                    |                                                                                                           |

| Product Reference             |          | TR-30+                                                                                                     | TS-30+              | TR-35+             | TS-35+                                  |
|-------------------------------|----------|------------------------------------------------------------------------------------------------------------|---------------------|--------------------|-----------------------------------------|
| Area of Classification (Dust) |          | Zones 21 and 22 Dust Groups IIIA and IIIB                                                                  |                     |                    | Zones 21 & 22 Dust Groups IIIA and IIIB |
| Max Surface Temp. (Dust)      |          | T130°C                                                                                                     |                     |                    |                                         |
| Ambient Temperature           |          | -30° to +40 / 55°C                                                                                         | -20°C to +40 / 55°C | -30° to +40 / 55°C | -20° to +40 / 55°C                      |
|                               |          | Maximum ambient temperature is for use only with certain specified cells, as per product instructions.     |                     |                    |                                         |
| Certificate                   |          | ATEX Baseefa 07ATEX0091X<br>IECEX BAS 06.0089X                                                             |                     |                    |                                         |
| Enclosure                     |          | Impact Resistant Thermoplastic, Chemical Resistant, Static Dissipative                                     |                     |                    |                                         |
| Lens                          |          | Toughened Glass 4mm                                                                                        |                     |                    |                                         |
| Beam Type                     |          | Medium Spot with Wide-Angle Flood of Fringe Light                                                          |                     |                    |                                         |
| Light Source:                 | Part No. | TP-300                                                                                                     |                     |                    |                                         |
|                               | Power    | Torch LED Module                                                                                           |                     |                    |                                         |
|                               | Output   | Up to 130 lm                                                                                               |                     |                    |                                         |
|                               | Life     | 25,000hrs+ (Fitted for Life)                                                                               |                     |                    |                                         |
| Power Source:                 | Part No. | 2 x H-20 (2 x LR-20 Cell suitable for 55° Maximum Ambient Temperature) (Batteries not supplied with torch) |                     |                    |                                         |
|                               | Type     | LR20 Primary Cells to IEC60086                                                                             |                     |                    |                                         |

| Product Reference     |       | TR-30+                                                        | TS-30+  | TR-35+  | TS-35+  |
|-----------------------|-------|---------------------------------------------------------------|---------|---------|---------|
|                       | Power | 2 x 1.5v                                                      |         |         |         |
| Low Battery Indicator |       | Yes                                                           |         |         |         |
| Light Duration        |       | Up to 14 hours to low power indicator<br>Up to 17 hours total |         |         |         |
| Ingress Protection    |       | IP67                                                          |         |         |         |
| Weight (inc. cells)   |       | 0.500kg                                                       | 0.475kg | 0.500kg | 0.475kg |

- The maximum ambient temperature is for use only with certain specified cells, as per product instructions.
- All information has been gathered under laboratory conditions, the user must regard the values given as approximate.
- Changes may be made to the above specification without notification, details are available on request.

## По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

**Россия** +7(495)268-04-70

**Казахстан** +(727)345-47-04

**Беларусь** +(375)257-127-884

**Узбекистан** +998(71)205-18-59

**Киргизия** +996(312)96-26-47

эл.почта: [wft@nt-rt.ru](mailto:wft@nt-rt.ru) || сайт: <https://wolfsafety.nt-rt.ru/>